

Oil and Water Level Meters

Geotech Interface Probe With Float

The Geotech Interface Probe With Float is a portable, reel-mounted instrument that provides measurements of liquids lighter and heavier than water. When the probe is lowered down a well and contacts the product layer, a solid tone and red light alarm is activated at the reel. When the probe detects water, the tone begins to oscillate and the light changes to green.

FEATURES

- Extremely durable polypropylene storage reel with rugged aluminum frame
- Highly accurate Kynar® coated steel tape marked in engineering or metric increments
- Stainless steel conductors for durability
- PTFE and stainless steel probe with spring strain relief
- Audible and visible alarms activated on reel when probe contacts product and water
- Auto shut-off circuit to extend battery life
- Easily replaced 9 volt battery
- Water resistant padded carrying case to protect instrument
- Built in reel hanger and included tape guide for longer tape life.



Geotech Interface Probe With Float
includes padded carrying case and tape guide

SPECIFICATIONS

Size:	Reel	13" H x 11" W x 7" D (33 cm H x 30 cm W x 18 cm D)
	Probe	1.5" O.D. x 8.9" L (3.8 cm O.D. x 22 cm L)
Length/Weight:		100' (30 m) = 9 lbs. (4 kg)
		200' (60 m) = 11 lbs. (5 kg)
		300' (100 m) = 14 lbs. (6 kg)
Accuracy:		100th of a foot/100' (3mm/30 m) per Federal Specification GGG-T-106E
Material:	Reel	Polypropylene and aluminum
	Tape	Kynar® coated steel
	Probe	PTFE, Viton® and stainless steel
Power:		9 Volt DC alkaline battery
Alarm:		Audible and Visual
Warranty:		1 year

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.

2650 East 40th Avenue • Denver, Colorado 80205

(303) 320-4764 • **(800) 833-7958** • FAX (303) 322-7242

email: sales@geotechenv.com website: www.geotechenv.com